Engine

Liigiile	
Туре	Turbo flat engine with gasoline particulate filter (GPF)
No. of cylinders	4
Valves/cylinders	4
Displacement	1,988 cm ³
Bore	91.0 mm
Stroke	76.4 mm
Max. power output	220 kW (300 PS)
at engine speed	6,500 rpm
Max. torque	380 Nm
at engine speed	2,150 – 4,500 rpm
Max. output per litre	111 kW/I (151 PS/I)
Compression ratio	9.5:1
Maximum engine speed	7,500 rpm
Cooling system	Water cooling with thermal management and switchable water pump
Valve control	Camshaft adjustment and VarioCam Plus valve lift adjustment for intake and exhaust
Oil supply	Integrated dry sump lubrication and demand-controlled oil pump
Engine charging	Mono turbocharging
Intercooling	Indirect intercooling (two low-temperature air-water radiators and one water-intercooler)
Exhaust system	Dual-branch exhaust system with central stainless steel tailpipe (high-gloss)

The technical data may vary from country to country

Power transmission

Drive system	Mid-engine, rear-wheel drive
Transmission	Seven-speed Porsche dual clutch transmission; Porsche Torque Vectoring (PTV) with mechanical rear differential lock
Gear ratios	
1 st gear	3.91
2 nd gear	2.29
3 rd gear	1.65
4 th gear	1.3
5 th gear	1.08
6 th gear	0.88
7 th gear	0.62
Reverse gear	3.55
Rear axle	3.62

Chassis

Suspension and damping	PASM sports chassis (-20 mm); 20-millimetre-lower steel suspension and hydraulic gas-filled vibration dampers; Porsche Active Suspension Management (PASM)
Front axle	Lightweight spring-strut suspension (McPherson type, Porsche-optimized)
Rear axle	Lightweight spring-strut suspension (McPherson type, Porsche-optimized)
Steering	Electromechanical power steering with variable steering ratio and steering pulse input
Steering ratio	15.0:1 (centre position) to 12.5:1
Steering wheel diameter	360 mm
Turning circle diameter	10.98 m
Vehicle stability system	Porsche Stability Management (PSM) incl. ABS with extended brake functions

Brakes

Brake system	Four-piston aluminium monobloc fixed-calliper brakes at the front and rear; electric parking brake
	ieai, eieotiio paikiily biake
Brake discs, front axle	Grey cast iron; internally vented and perforated
Diameter	330 mm
Thickness	28 mm
Brake discs, rear axle	Grey cast iron; internally vented and perforated
Diameter	299 mm
Thickness	20 mm

Wheels and tyres

Wheels and tyres, front	8 J x 20 ET 57 with 235/35 ZR 20 tyres
Wheels with tyres, rear	10 J x 20 ET 45 with 265/35 ZR 20 tyres

Dimensions

Length	4,379 mm
Width (with door mirrors)	1,801 mm (1,994 mm)
Height	1,276 mm
Wheelbase	2,475 mm
Track width, front	1,528 mm
Track width, rear	1,534 mm

Luggage volumes and weights

Luggage volumes	425 I (front 150 I, rear 275 I)
Unladen weight (DIN)	1,380 kg
Allowable gross weight	1,685 kg

Performance

Top speed	275 km/h
Acceleration	
0-60 mph	4.7 s
0-60 mph with Sport+	4.5 s
0-100 km/h	4.9 s
0-100 km/h with Sport+	4.7 s
0-160 km/h	11.1 s
0-160 km/h with Sport+	10.8 s
0-200 km/h	18.1 s
0-200 km/h with Sport+	17.8 s

Fuel and emissions

Emissions standard	EURO 6d-Temp (EU6 AG)
Fuel type	Super Plus (98 RON)
Fuel consumption	
Urban	10.8 l/100 km
Extra-urban	6.2 I/100 km
Combined	7.9 I/100 km
CO ₂ emissions	
Combined	180 g/km
Efficiency class in Germany	E
Fuel tank capacity	541

Aerodynamics

Drag coefficient c _d	0.3
Frontal area A	2.01 m ²
c _w x A	0.603

All information refers to the EU model.